

General Information for “Boating & RV”

Suitable for all vented, fresh or salt water based wastewater systems

Treat system as per conventional rural septics and Bio cycles, Use Bio Safe cleaners etc.

Usage Directions: Shake Before Use then pour **ProPower** directly into tank or through fixtures such as toilets, Sinks etc. with enough water to ensure your tank does not go dry. Alternatively pour **ProPower** into a bucket of water and pour into the above mentioned fixtures.

Tanks should preferably be emptied and rinsed prior to first use but not mandatory providing chemicals have not been added in the 2 weeks prior.

For cassette toilets enter ProPower into cassette the first day of regular use and then continue to use regularly.

ProPower will continue cleaning as long as water remains in tank

Visible Particles are natural and do not reduce effectiveness

ProPower is safe for People, Animals and plants, in case of any irritation rinse/ wash with clean water

ProPower Boating & RV

First Time use

Boats: Add 120ml to tanks less than 240 litres

Add 240ml to tanks larger than 240 litres

Portable Toilets/ Cassettes: Add 60ml

Regular Use

Boats: Add 60ml down toilet with enough water to ensure the tank does not go dry for tanks under 240 litres (frequent pumping is unnecessary)

Add 120ml down toilet with enough water to ensure the tank does not go dry for tanks larger than 240 litres (frequent pumping is unnecessary)

Portable Toilets/Cassettes: Add 30ml after each pump out (frequent pumping is not necessary).